



A7 Receipt Printer

The Printer with a Compact design and improved user interface application



System



A7		
Printing Method	3" Jam-free direct thermal	
Printing Speed	170 mm/sec max	
Dot Density (DPI)	203.2	
Dot Pitch (mm)	0.125*0.125	
Effective Printing Width	74mm, 576dots	
Printing Direction	Unidirectional with friction feed	
Character/Line	Font A	(14*28) 42 columns
	Font B	(10*20) 58 columns
Paper	Type	Thermal paper
	Width	79.5mm (±0.5mm)
	Thickness	0.07mm
	Roll diameter	83 Ømm
Reliability	TPH Life	100km
	MCBF	60,000,000 lines
Character/Set	Alphanumeric character	95
	Extended graphic	128 x 35 page
Barcode	EAN-8, EAN-13, CODE39, CODE93, CODE128, ITF, UPC-A, UPC-E, CODABAR	
Emulation	ESC/POS command compatible	
Driver	Windows / OPOS	
Interface	Serial / USB / USB+Serial combo	
Power	DC 24V, 2.5A	
Data Buffer	4 Kbyte	
Cutting	Life	700,000 cuts
	Cutting method	Partial Cut
Temperature	Operation	0 ~ 40°C
	Storage	-20 ~ 60°C

* Product is applied locally with different specifications and is also capable of being altered without prior notice.